

Reliable, high performance, low cost DISPLAY

S401 OLED display with ModBUS interface



OLED

**High
brightness**

70 cd/m²

**High
definition**

128x64 pixel

**Compact
size**

40 mm depth

Visualization

Up to 30
measures

Setup

Via software
or menu keys

**Master
functions**

27 math functions,
20 readings,
20 writings

Alarms

Hysteresys
and thrershold
activation

**Minimum
wiring**

Nr 2 RS485
ModBUS interfaces

 **SENECA**

via Germania, 34 • 35127 Padova - Italy - Ph +39 049 87.05.359 (.408)
Fax +39 049 87.06.287 • www.seneca.it • info@seneca.it

SLine_0901EN - Document subject to modifications and revisions. Reproduction forbidden if not authorized.

Reliable, high performance, low cost DISPLAY

S311 Line Modular displays



Scalable display

4, 6, 8, 4+7 digits

Universal input

Analog, digital, temperature

Retransmission

Analog or digital output

Power supply wide range

80-265 Vac;
10-40 Vdc / 19-28 Vac
Power transducers

Accuracy

0,1% class precision
A/D conversion
14-16 bit

Alarms (relay)

Hysteresis and threshold control

Multiple visualization

Real-time, integrated, totalized measured values

Special functions

Average, filter frequency, VLF mode, access via password



via Germania, 34 • 35127 Padova - Italy - Ph +39 049 87.05.359 (.408)
Fax +39 049 87.06.287 • www.seneca.it • info@seneca.it

SLine_0901EN - Document subject to modifications and revisions. Reproduction forbidden if not authorized.